

ASSA ABLOY

Issue date: 08-08-2017 Expiry date: 13-12-2018

ACCESSORIES Pyropanel Auto Bolt

DESCRIPTION

Automatic bolt for fire door pairs, which is recessed into the head of the non active leaf, and automatically bolts the non-active leaf when the active leaf returns to the closed position.

FEATURES

- Suitable for Pyropanel Fire Rated pair doorsets.
- Designed to securely hold the non-active leaf closed in the event of a fire scenario.
- Fire Rated up to 4 hrs.

O


- Fail safe.
- Manufactured in Australia.
- Easy to install.
- Head of the door frame requires a rectangular hole.

 \cap


C

(D)

9C



Front elevation showing disengaged Auto bolt with active door leaf open.



Front elevation showing engaged Auto bolt after active door leaf is closed.

95mm 20mm 22mm 22mm 21mm 21mm Side elevation End elevation

HOW TO SPECIFY

"Pyropanel Fire Rated Doorset Pair to include Pyropanel Fire Rated Auto bolt to non-active leaf"...

Pyropanel Developments Pty Ltd

235 Huntingdale Rd, Oakleigh, Vic 3166 Ph: **(03) 9837 8500** Fax: (03) 9837 8550 Email: **sales@pyropanel.com.au** Web: **www.pyropanel.com.au**

Distributed by: Holland Fire Doors & Windows 23 Saggart Field Rd, Minto, NSW, 2566 Ph: **9603 8500** Email: **sales@hollandfiredoors.com.au**

Pyropanel Developments has a policy of continuous improvement and reserves the right to change methods and specifications without notice. Note: The Tech Sheet is an uncontrolled document, If printed please refer to the Tech-Sheet on the website to check if this document is valid.