

Issue date: 10-09-2017 Expiry date: 31-12-2018



ADLOT 2 hr fire rated, 40 Rw, Single Acoustic / Smoke / Fire door

DESCRIPTION

Pyropanel AS-FRB-A is a, 2 hour fire rated 55mm nominal single leaf acoustic door (up to 40 Rw). This door comes standard with ply faces.

APPLICATIONS

Ideal for applications that requires up to 2 hours of fire resistance and an acoustic rating of up to 40 Rw, such as warehouses and factories.

FEATURES

Acoustic Rating

- Up to 40 Rw (see seal combinations in table below)
- Fire Resistance
- -/120/30

Door Configuration

Single leaf

Thickness

55mm (Nominal)

Size

Maximum Size - 2400 x 1020

Frame

Packed steel frame (2 hr)

Finish

Ply or steel to both faces.

Seal combinations

Door Type	Perimeter	Bottom	Rw
AS-FRB-A1#	Euroseal	RP8si or RP38si + Pyrosill	40
AS-FRB-A2	RP39	RP8si + Pyrosill	40
AS-FRB-A3#	Euroseal	RP38si	39
AS-FRB-A4	RP39	RP38si	39
AS-FRB-A5#	Euroseal	RP8si	34

These doors meet the NCC requirement for a smoke door.

Pyropanel Developments Pty Ltd


Unit 1, 97 Lewis Rd, Wantirna South, Vic 3152 Ph: (03) 9837 8500 Fax: (03) 9837 8550 Email: sales@pyropanel.com.au Web: www.pyropanel.com.au

OPTIONAL EXTRAS

- Pre-hung in steel frame
- Stainless steel faces
- Pyropanel Pyrodur 13mm Vision panels 300 x 200 or 600 x 100mm. Glass rated to 38 Rw. note - The inclusion of a vision panel will cause a slight reduction in acoustic rating.
- Kick Panels of 1mm Stainless Steel to selected height.
- Some models meet the NCC requirement for a smoke door.

INSTALLATION

Door frame must be tightly sealed against wall structure using Pyropanel Multiflex fire and acoustic sealant. Steel frames will require packing with Pyropanel FR Board, Fire rated plaster, concrete or mortar or Pyropanel light weight M4 Mortar to achieve desired acoustic and fire rating.



HOW TO SPECIFY

"Door to be a Pyropanel AS-FRB-A1* acoustic door with -/120/30 FRL* and installed in a packed steel door frame*". * denotes example - delete, change or specify as required

Distributed by:

Holland Fire Doors & Windows 23 Saggart Field Rd, Minto, NSW, 2566

Ph: **9603 8500** Email: **sales@hollandfiredoors.com.au**

Pyropanel Developments has a policy of continuous improvement and reserves the right to change methods and specifications without notice. Note: The Tech Sheet is an uncontrolled document, If printed please refer to the Tech-Sheet on the website to check if this document is valid.